

ACE DEKTON DRILL

RECOMMENDED WORKING PARAMETERS



UCS Drills are perfect for Ultra Compact Surfaces including Dekton, Neolith and Lapitec. They come with dual fitting, 1/2" gas and M14, which means they can be used on either CNC machines or water fed machines for use by hand.

To achieve the best results with your drill they should always be used with water and run at the recommended working parameters which can be found below.



RECOMMENDED WORKING PARAMETERS

Ø	RPM	FEED SPEED
06 to 25	5,000	30mm/min
28 to 40	4,000	30mm/min
45 to 68	3,000	30mm/min
80 to 100	2,000	30mm/min

CODES AND SIZES AVAILABLE

CODE	Ø	FITTING
ACE-DR-DEK-06	06mm	Dual Fitting
ACE-DR-DEK-08	08mm	Dual Fitting
ACE-DR-DEK-10	10mm	Dual Fitting
ACE-DR-DEK-16	16mm	Dual Fitting
ACE-DR-DEK-20	20mm	Dual Fitting
ACE-DR-DEK-22	22mm	Dual Fitting
ACE-DR-DEK-25	25mm	Dual Fitting
ACE-DR-DEK-30	30mm	Dual Fitting
ACE-DR-DEK-35	35mm	Dual Fitting
ACE-DR-DEK-40	40mm	Dual Fitting
ACE-DR-DEK-45	45mm	Dual Fitting
ACE-DR-DEK-50	50mm	Dual Fitting
ACE-DR-DEK-60	60mm	Dual Fitting
ACE-DR-DEK-68	68mm	Dual Fitting
ACE-DR-DEK-80	80mm	Dual Fitting

CALL US ON **01268 766807**

or visit our website www.vetrotooling.com
email us sales@vetrotooling.com